

C180-SD

SIMPLE DISPENSATION

This converting machine is focussed for basic dispensing jobs and developed to apply RFID (radio frequency), anti-theft, or electromagnetic tags over any type of roll labels printed or white labels, maintaining the same position to finally re-reel into a single output roll. To the standard machine C180-SD could be added a verification & marking system upon request.



TECHNICAL INFORMATION

Machine speed	Max. 50 mt. / min (Depending on material).
Tolerance	+1 mm
Energy supply:	3 – N/PE, 400V, 50HZ, 7A
Compressed air:	6 Bar
Net weight	600 Kg

Label dispenser 256**

Dispensing speed	Max. 50 mt. / min (Depending on label pitch)
Label material	Converted self – adhesive label material with adhesive
Maximum width (including backing paper)	Up to 160 mm
Label length	5 to 600 mm
Label roll unwinder outer diameter	Up to 300 mm
Label roll rewinder outer diameter	Up to 200 mm
Core labels inner diameter	3"

Main label specifications

Maximum roll width	Up to 180 mm
Maximum roll length	Without limit.
Minimum label width	25 mm
Minimum label length	19 mm
Ø max. unwinding labels	400 mm
Ø maxi rewinding labels	400 mm
Core labels inner diameter	3"

TYPE OF WORK

